



POLISHED CONCRETE DYE

Safety Data Sheet

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name REFINE-MAXX
POLISHED CONCRETE DYE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Dye for cementitious materials

1.3. Details of the supplier of the safety data sheet

JON-DON
400 MEDINAH ROAD
ROSELLE, IL 60172

1.4. Information number

Number :800-556-6366

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US) Eye
Irrit. 2A H319

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS07

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H319 - Causes serious eye irritation

Precautionary statements (GHS-US) : P264 - Wash ... thoroughly after handling
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P305 + P351 + P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337 + P313 - If eye irritation persists: Get medical advice/attention

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
------	--------------------	---	-------------------------

POLISHED CONCRETE DYE

Safety Data Sheet

Proprietary Component 1	(CAS No) Trade Secret	Trade Secret	Not classified
Proprietary Component 2	(CAS No) Trade Secret	Trade Secret	Flam. Liq. 4, H227
Proprietary Component 3	(CAS No) Trade Secret	Trade Secret	Not classified
Proprietary Component 4	(CAS No) Trade Secret	Trade Secret	Not classified
Proprietary Component 5	(CAS No) Trade Secret	Trade Secret	Not classified
Proprietary Component 6	(CAS No) Trade Secret	Trade Secret	Not classified

4.1. Description of first aid measures

First-aid measures after inhalation : Seek medical attention.

First-aid measures after skin contact : Flush with water for at least 15 minutes. Seek medical attention if irritation develops or persists. First-aid measures after eye contact : Immediately flush eyes with plenty of water for at least 15 minutes. If irritation persists get medical attention.

Symptoms/injuries after inhalation : None under normal use. Symptoms/injuries after skin contact : None under normal use.

Symptoms/injuries after eye contact : Causes serious eye irritation. Symptoms/injuries after ingestion : May be harmful if swallowed.

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire. Unsuitable extinguishing media : None.

5.2. Special hazards arising from the substance or mixture

Fire hazard : None known. Explosion hazard : None known.

5.3. Advice for firefighters

Protection during firefighting : Firefighters should wear full protective gear.

release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Stop the flow of material, if this is without risk.

Methods for cleaning up : Confine spill and soak up with absorbent. Place in an approved container and dispose in accordance with local, state and federal regulations.

POLISHED CONCRETE DTE

Safety Data Sheet

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in dry, cool, well-ventilated area.

7.3. Specific end use(s)

Dye for cementitious materials

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Proprietary Component 2 (Trade Secret)

USA ACGIH	ACGIH TWA (ppm)	10 ppm
-----------	-----------------	--------

Proprietary Component 3 (Trade Secret)

USA ACGIH	ACGIH TWA (mg/m ³)	0.5 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1 mg/m ³

8.2.

Exposure controls

Appropriate engineering controls : Provide adequate ventilation.
Hand protection : Use impervious gloves such as neoprene, nitrile, or rubber for hand protection.
Eye protection : Chemical goggles or safety glasses.
Skin and body protection : Wear suitable working clothes.
Respiratory protection : If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Multi-colored.
Odor :
Mild odor
Odor threshold :
No data available
pH : No data available
Relative evaporation rate (butyl acetate=1) :
No data available
Melting point : No data available
Freezing point :
No data available
Boiling point :
No data available
Flash point : No data available
12/18/17 EN (English US)

POLISHED CONCRETE DYE

Safety Data Sheet

Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Flammability (solid, gas)	:	No data available
Vapor pressure	:	No data available
Relative vapor density at 20 °C	:	No data available
Relative density	:	No data available
Solubility	:	Miscible with water.
Log Pow	:	No data available
Log Kow	:	No data available
Viscosity, kinematic	:	No data available
Viscosity, dynamic	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Explosive limits	:	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Will not occur.

10.4. Conditions to avoid

None.

10.5. Incompatible materials

Not determined.

10.6. Hazardous decomposition products

Not determined.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified
EN (English US)

POLISHED CONCRETE DYE

Safety Data Sheet

Proprietary Component 2 (Trade Secret)	
LD50 oral rat	3384 mg/kg
LD50 dermal rabbit	2700 mg/kg
ATE US (oral)	3384.00000000 mg/kg
ATE US (dermal)	2700.00000000 mg/kg

Proprietary Component 5 (Trade Secret)	
LD50 oral rat	29000 mg/kg
LD50 dermal rabbit	> 20 ml/kg
ATE US (oral)	29000.00000000 mg/kg

Proprietary Component 6 (Trade Secret)	
LD50 oral rat	20000 mg/kg
LD50 dermal rabbit	20800 mg/kg
ATE US (oral)	20000.00000000 mg/kg body weight
ATE US (dermal)	20800.00000000 mg/kg body weight

Skin corrosion/irritation : Not classified
 Serious eye damage/irritation : Causes serious eye irritation.
 Respiratory or skin sensitization : Not classified
 Germ cell mutagenicity : Not classified
 Carcinogenicity : Not classified

Proprietary Component 3 (Trade Secret)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified
 Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Proprietary Component 2 (Trade Secret)	
LC50 fish 1	1300 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 1	> 100 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)

Proprietary Component 5 (Trade Secret)	
LC50 fish 1	> 1000 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static])

POLISHED CONCRETE DYE

Safety Data Sheet

EC50 Daphnia 1	> 500 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 1	> 500 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)

Proprietary Component 6 (Trade Secret)

LC50 fish 1	51600 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 other aquatic organisms 1	19000 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)
LC50 fish 2	41 - 47 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])

POLISHED CONCRETE DYE

Safety Data Sheet

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Proprietary Component 2 (Trade Secret)

BCF fish 1	(no bioconcentration expected)
------------	--------------------------------

Proprietary Component 5 (Trade Secret)

Log Pow	0.48 (at 25 °C)
---------	-----------------

Proprietary Component 6 (Trade Secret)

BCF fish 1	< 1
------------	-----

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations.

Transport information

In accordance with DOT

Not a dangerous good

SECTION 15: Regulatory information

15.1. US Federal regulations

Proprietary Component 2 (Trade Secret)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag

T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA. Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

Proprietary Component 3 (Trade Secret)

POLISHED CONCRETE DYE

Safety Data Sheet

Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

Proprietary Component 6 (Trade Secret)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag	Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.
--------------------------	--

15.2. US State regulations

Proprietary Component 3 (Trade Secret)

U.S. - Massachusetts - Right To Know List
 U.S. - Minnesota - Hazardous Substance List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List


Proprietary Component 6 (Trade Secret)

U.S. - Minnesota - Hazardous Substance List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List

Full text of H-phrases:

Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 4	Flammable liquids Category 4
H227	Combustible liquid
H319	Causes serious eye irritation

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.
 NFPA fire hazard : 1 - Must be preheated before ignition can occur.
 NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product