

# SAFETY DATA SHEET

## PROSOCO, Inc.



PROSOCO  
Version 3

Issue Date 18-Dec-2014

Revision Date 26-Feb-2016

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### Product identifier

**Product Name** Consolideck® GemTone Stain Blue Stone

#### Other means of identification

**Product Code** 46115

#### Recommended use of the chemical and restrictions on use

**Recommended Use** Restricted to professional users.

**Uses advised against** No information available

#### Details of the supplier of the safety data sheet

##### **Manufacturer Address**

PROSOCO, Inc.  
3741 Greenway Circle  
Lawrence, Kansas 66046

##### **Emergency telephone number**

**8:00 AM – 5:00 PM CST Monday-Friday** 785-865-4200  
**NON-BUSINESS HOURS (INFOTRAC)** 800-535-5053

### 2. HAZARDS IDENTIFICATION

#### Classification

Serious eye damage/eye irritation

Category 2A

#### Label elements

#### Emergency Overview

##### **Warning**

##### **Hazard statements**

Causes serious eye irritation



**Appearance** dark blue

**Physical state** Liquid

**Odor** Slight

#### **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection

#### **Precautionary Statements - Response**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

**Hazards not otherwise classified (HNOC)**

**Other Information**

- May be harmful in contact with skin
  - May be harmful if swallowed
  - May cause skin irritation
- No information available

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Diethylene glycol monobutyl ether	112-34-5	60 - 100	*
Benzyl Alcohol	100-51-6	7 - 13	*
Organic Chrome Complex	Proprietary	1 - 5	*
Proprietary - Blue Colorant	Undisclosed	1 - 5	*
Sodium dioctyl sulfosuccinate	577-11-7	1 - 5	*
Organic Chrome Complex	Proprietary	1 - 5	*
Organic Chrome Complex	Proprietary	1 - 5	*

\* The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**First aid measures**

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	If symptoms persist, call a physician. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	Remove to fresh air. If symptoms persist, call a physician.
<b>Ingestion</b>	Do NOT induce vomiting. Rinse mouth. Drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician.
<b>Self-protection of the first aider</b>	Use personal protective equipment as required.

**Most important symptoms and effects, both acute and delayed**

**Symptoms** Causes serious eye irritation. May cause skin irritation.

**Indication of any immediate medical attention and special treatment needed**

**Note to physicians** Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media**

Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.

**Unsuitable Extinguishing Media** Caution: Use of water spray when fighting fire may be inefficient.

**Specific hazards arising from the chemical**

No information available.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures****Personal precautions**

Use personal protective equipment as required. Avoid contact with eyes and skin.

**Environmental precautions****Environmental precautions**

Prevent entry into waterways, sewers, basements or confined areas. Do not flush into surface water or sanitary sewer system. Prevent product from entering drains. See Section 12 for additional ecological information.

**Methods and material for containment and cleaning up****Methods for containment**

Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up**

Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

**7. HANDLING AND STORAGE****Precautions for safe handling****Advice on safe handling**

Ensure adequate ventilation, especially in confined areas. Use personal protective equipment as required. Use with local exhaust ventilation. Avoid contact with skin, eyes or clothing. Avoid breathing vapors or mists.

**Conditions for safe storage, including any incompatibilities****Storage Conditions**

Keep out of the reach of children. Keep containers tightly closed in a cool, well-ventilated place. Keep in properly labeled containers.

**Incompatible materials**

Incompatible with strong acids and bases. Incompatible with oxidizing agents.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Control parameters****Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Organic Chrome Complex	-	TWA: 0.5 mg/m <sup>3</sup> Cr (vacated) TWA: 0.5 mg/m <sup>3</sup> Cr (vacated) Ceiling: 0.1 mg/m <sup>3</sup> CrO <sub>3</sub> applies to any operations or sectors for which the Hexavalent Chromium standard [29 CFR 1910.1026] is stayed or is otherwise not in effect	IDLH: 15 mg/m <sup>3</sup> Cr(VI) IDLH: 25 mg/m <sup>3</sup> Cr(III) TWA: 0.0002 mg/m <sup>3</sup> Cr TWA: 0.5 mg/m <sup>3</sup> Cr
Organic Chrome Complex	-	TWA: 0.5 mg/m <sup>3</sup> Cr (vacated) TWA: 0.5 mg/m <sup>3</sup> Cr (vacated) Ceiling: 0.1 mg/m <sup>3</sup> CrO <sub>3</sub> applies to any operations or sectors for which the Hexavalent Chromium	IDLH: 15 mg/m <sup>3</sup> Cr(VI) IDLH: 25 mg/m <sup>3</sup> Cr(III) TWA: 0.0002 mg/m <sup>3</sup> Cr TWA: 0.5 mg/m <sup>3</sup> Cr

		standard [29 CFR 1910.1026] is stayed or is otherwise not in effect	
Organic Chrome Complex	-	TWA: 0.5 mg/m <sup>3</sup> Cr (vacated) TWA: 0.5 mg/m <sup>3</sup> Cr (vacated) Ceiling: 0.1 mg/m <sup>3</sup> CrO <sub>3</sub> applies to any operations or sectors for which the Hexavalent Chromium standard [29 CFR 1910.1026] is stayed or is otherwise not in effect	IDLH: 15 mg/m <sup>3</sup> Cr(VI) IDLH: 25 mg/m <sup>3</sup> Cr(III) TWA: 0.0002 mg/m <sup>3</sup> Cr TWA: 0.5 mg/m <sup>3</sup> Cr

NIOSH IDLH *Immediately Dangerous to Life or Health*

**Other Information** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

### Appropriate engineering controls

**Engineering Controls** None under normal use conditions.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear protective gloves and protective clothing.

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**General Hygiene Considerations** When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Regular cleaning of equipment, work area and clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	Liquid	<b>Odor</b>	Slight
<b>Appearance</b>	dark blue	<b>Odor threshold</b>	No information available
<b>Color</b>	dark blue		
<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>	
pH	Not Applicable		
Melting point/freezing point	0 °C / 32 °F		
Boiling point/boiling range	No information available		
Flash point	> 100 °C / > 212 °F	ASTM D 3278	
Evaporation rate	No information available		
Flammability (solid, gas)	No information available		
Flammability Limits in Air			
Upper flammability limits	No information available		
Lower flammability limit	No information available		
Vapor pressure	No information available		
Vapor density	No information available		
Specific Gravity	1.0 (0.9 -1.1)		
Water solubility	Soluble in water		
Solubility in other solvents	No information available		
Partition coefficient	No information available		
Autoignition temperature	No information available		
Decomposition temperature	No information available		
Kinematic viscosity	No information available		

**Dynamic viscosity** No information available

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

None under normal processing.

### Conditions to avoid

Extremes of temperature and direct sunlight.

### Incompatible materials

Incompatible with strong acids and bases. Incompatible with oxidizing agents.

### Hazardous Decomposition Products

None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

<b>Product Information</b>	Causes serious eye irritation May cause skin irritation
<b>Inhalation</b>	Avoid breathing vapors or mists. May be harmful if inhaled.
<b>Eye contact</b>	Avoid contact with eyes. Causes serious eye irritation.
<b>Skin Contact</b>	Avoid contact with skin. May cause irritation.
<b>Ingestion</b>	Do not taste or swallow. Harmful if swallowed.

### Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Diethylene glycol monobutyl ether 112-34-5	= 3384 mg/kg ( Rat )	= 2700 mg/kg ( Rabbit )	-
Benzyl Alcohol 100-51-6	= 1230 mg/kg ( Rat )	= 2000 mg/kg ( Rabbit )	= 8.8 mg/L ( Rat ) 4 h
Sodium dioctyl sulfosuccinate 577-11-7	= 1900 mg/kg ( Rat )	= 10000 mg/kg ( Rabbit )	-

### Information on toxicological effects

**Symptoms** May cause respiratory irritation. May cause skin irritation.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization** No information available.  
**Germ cell mutagenicity** No information available.  
**Carcinogenicity** This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.

Chemical Name	ACGIH	IARC	NTP	OSHA
Organic Chrome Complex	-	Group 3	-	-
Organic Chrome Complex	-	Group 3	-	-
Organic Chrome Complex	-	Group 3	-	-

*IARC (International Agency for Research on Cancer)*

*Not classifiable as a human carcinogen*

**Reproductive toxicity** No information available.

<b>STOT - single exposure</b>	No information available.
<b>STOT - repeated exposure</b>	No information available.
<b>Chronic toxicity</b>	Avoid repeated exposure. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects.
<b>Target Organ Effects</b>	blood, Eyes, kidney, liver, lungs, Respiratory system, Skin.
<b>Aspiration hazard</b>	No information available.

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document .

<b>ATEmix (oral)</b>	2800 mg/kg
<b>ATEmix (dermal)</b>	3014 mg/kg mg/l
<b>ATEmix (inhalation-dust/mist)</b>	14.7 mg/l

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Diethylene glycol monobutyl ether 112-34-5	100: 96 h Desmodesmus subspicatus mg/L EC50	1300: 96 h Lepomis macrochirus mg/L LC50 static	-	2850: 24 h Daphnia magna mg/L EC50 100: 48 h Daphnia magna mg/L EC50
Benzyl Alcohol 100-51-6	35: 3 h Anabaena variabilis mg/L EC50	460: 96 h Pimephales promelas mg/L LC50 static 10: 96 h Lepomis macrochirus mg/L LC50 static	-	23: 48 h water flea mg/L EC50
Sodium dioctyl sulfosuccinate 577-11-7	-	20 - 40: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 24: 96 h Oncorhynchus mykiss mg/L LC50 static 37: 96 h Lepomis macrochirus mg/L LC50 static	-	36: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical Name	Partition coefficient
Benzyl Alcohol 100-51-6	1.1

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods**

<b>Disposal of wastes</b>	Disposal should be in accordance with applicable regional, national and local laws and regulations.
<b>Contaminated packaging</b>	Do not reuse container.
<b>US EPA Waste Number</b>	D007

This product contains one or more substances that are listed with the State of California as a hazardous waste.

**14. TRANSPORT INFORMATION**

DOT Not Regulated for all modes of transportation.

**15. REGULATORY INFORMATION**

**International Inventories**

**TSCA** Complies  
**DSL/NDSL** Complies

**Legend:**

*TSCA - United States Toxic Substances Control Act Section 8(b) Inventory*  
*DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List*

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Organic Chrome Complex -	-	1 - 5	1.0
Organic Chrome Complex -	-	1 - 5	1.0
Organic Chrome Complex -	-	1 - 5	1.0

**SARA 311/312 Hazard Categories**

**Acute health hazard** Yes  
**Chronic Health Hazard** No  
**Fire hazard** No  
**Sudden release of pressure hazard** No  
**Reactive Hazard** No

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Organic Chrome Complex	-	X	-	-
Organic Chrome Complex	-	X	-	-
Organic Chrome Complex	-	X	-	-

**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

**US State Regulations**

**California Proposition 65**

This product does not contain any Proposition 65 chemicals

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Diethylene glycol monobutyl ether 112-34-5	X	-	X
Organic Chrome Complex	X	-	X
Organic Chrome Complex	X	-	X
Organic Chrome Complex	X	-	X
Ethanol 64-17-5	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health hazards 2	Flammability 1	Instability 0	Physical and Chemical Properties -
<b>HMIS</b>	Health hazards 2	Flammability 1	Physical hazards 0	Personal protection X

Prepared By Regulatory Department  
 Issue Date 18-Dec-2014  
 Revision Date 26-Feb-2016

Revision Note  
 SDS sections updated  
 2 3 6 7 8 11 12 15

**Disclaimer**

The information contained on the Safety Data Sheet has been compiled from data considered accurate. This data is believed to be reliable, but it must be pointed out that values for certain properties are known to vary from source to source. PROSOCO, Inc. expressly disclaims any warranty express or implied as well as any liability for any injury or loss arising from the use of this information or the materials described. This data is not to be construed as absolutely complete since additional data may be desirable when particular conditions or circumstances exist. It is the responsibility of the user to determine the best precautions necessary for the safe handling and use of this product for his unique application. This data relates only to the specific material designated and is not to be used in combination with any other material. Many federal and state regulations pertain directly or indirectly to the product's end use and disposal of containers and unused material. It is the purchaser's responsibility to familiarize himself with all applicable regulations.

**End of Safety Data Sheet**